



## DURALIFE® FULL SYNTHETIC CONTINUOUSLY VARIABLE TRANSMISSION FLUID CVT FLUID



**Duralife® Full Synthetic CVT Fluid** is designed with Synthetic base oils and the latest additive technology for Today's high-performance transmissions in Vehicles equipped with either chain or push belt Continuously Variable Transmissions (CVT). This CVT fluid provides full synchronization for gear shifting, excellent year-round protection, superior high-temperature and low-temperature operation, superior friction control and improves load-carrying ability, performance life in CVT application.

### APPLICATIONS:

**Duralife® Full Synthetic CVT Fluid** meets or exceeds the following Manufacturer's performance requirements.

Audi Multitronic, Audi /VW G-052-516-A2, G-052-180-A2/TL52 180

BMW 83 22 0 136 376, 83 22 0 429 154, EZL 799A

Chery CVT

Chrysler CVTF+4 /68044345 EA / Chrysler Jeep NS-2

Daihatsu Ammix CVT Fluid DC / Daihatsu CVT Fluid TC /CVTF-DFE /CVT Fluid DFC

Daihatsu Alumix Multi /Daihatsu ECO CVT

Dexron CVT

Dodge/Jeep NS-2, CVTF+4

Esso EZL799 (CVT)

Ford CVT 2/23/30/Ford CVT WSS M2C933-A(XT-7QCFT)/1490761/1490763

Ford Mercon C

Fuji ECVT, ICVT

Fujijyuuko I-CVT Fluid/ Fujijyuuko I-CVT Fluid FG

GM/Saturn (DEX-CVT, CVTF I-Green 2)

Honda Multimatic Fluid (HMMF), Honda HCF2, Honda Z-1, Honda CVT

Hyundai/Kia (SP III- CVT1)

Idemitsu CVTS-EX1

Jatco CVT 8 (JF016E/JF017E)

Mazda CVTF 3320

Mercedes-Benz 236.20, CVT 28

MG Rover EM-CVT

Mini Cooper EZL799A, ZF CVT V1

Mitsubishi CVT Fluid (NS-2/SP-III)/ Mitsubishi CVTF-J1

Mitsubishi Diaqueen CVT Fluid J1/Dia-Queen SST/ DiaQueenSSTF-1/CVTF-J4

Mitsubishi Invecs-III CVT, Sportsmode 6 CVT/MZ 320065

Mopar CVT Fluid+4

Nissan CVT NS-1/NS-2/NS-3

Peugeot, Citroen 9734.S2 for DCS 6 (Peugeot 4007, Citroen C-Crosser)

Punch CVT

Renault Elf Matic CVT

Shell Green 1V  
 Suzuki CVTFluid (TC/NS-2) / Suzuki CVT Oil/ Suzuki CVT Green 1&2/Green 1V/CVTF 3320  
 Subaru CVT Fluid NS-2 / ECVT/ iCVT/iCVT FG, Lineartronic chain CVT& CVT II Fluid,  
 K0425Y0710, Lineartronic High Torque (HT) CVT Fluid, CV-30, K0421Y0700  
 Toyota Super CVT Fluid TC / FE  
 Volvo MP S6 Powershift oil/ 1161838/ 1161839/Volvo 4959  
 ZF CVT VT1

**BENEFITS:**

- Compatibility in multiple CVT Transmission types.
- Suitable for some hydraulic transmissions, servo-controlled mechanisms and hydraulic systems.
- Superior friction control, oxidation control, anti-wear protection.
- Enhances slip-lock performance, anti-shudder protection.
- Excellent antifoam, antirust, anticorrosion properties.
- Maximizes equipment life by maintaining wear protection and oil film thickness.

**TYPICAL CHARACTERISTICS**

Test	Method	Typical results
API Gravity	ASTM D287	34
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.855
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	33.75 7.1
Brookfield Viscosity @ -40°C, cP	ASTM D2983	12,000
Viscosity Index	ASTM D2270	180
Flash Point , °C (°F)	ASTM D92	190 (374)
Pour Point , °C (°F)	ASTM D97	-48 (-54.4)
Foam test @ 93.5°C, ml	ASTM D892	0/0

*The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.*

**WARNING:**

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.  
 Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS Number 12091 database on our website at [www.amtecol.com](http://www.amtecol.com) OR scan the code for a direct link

